



## Hunan Huayuan display technology CO.,LTD

# HY8048C062L-HDMI V01

## TFT TOUCH MODULE

### SPECIFICATION

Standard code	Department	Rev No.
		V1.1
Checked by	Written by	Date
Jeff.P	Noah.L	2018-08




## CONTENTS

- 1、 GENERAL INFORMATION
- 2、 EXTERNAL DIMENSIONS
- 3、 ABSOLUTE MAXIMUM RATINGS
- 4、 ELECTRICAL CHARACTERISTICS
- 5、 CTP CHARACTERISTICS
- 6、 ELECTRO-OPTICAL CHARACTERISTICS
- 7、 INTERFACE DESCRIPTION
- 8、 INPUT TIMING
- 9、 RELIABILITY TEST CONDITIONS
- 10、 INSPECTION CRITERION
- 11、 PRODUCT PHOTOS

## 1、GENERAL INFORMATION

Item of general information	Contents	Unit
LCD Display Size(Diagonal)	6.2	inch
Module Structure	HDMI Display+ USB Touch PCB	-
Display Resolution	800RGB×480	pixel
Module Dimensions (W×H×T)	155.2×88.2×5.0	mm
Active Area Dirnensions (W×H)	137.52×77.23	mm
Pixel Pitch(W×H)	0.1719×0.1609	mm
Color Pixel Arrangement	RGB Stripe	-
Display Mode	Transmissive Type, Normally White Mode	-
Viewing Direction(Gray Inversion)	60° clock	-
Interface Type	LCD	HDMI type-E
	CTP	JST-SH 4pin
Numbers of Colors	16.7M	colors
CTP Structure Type	Cover Glass i' to Glass(G+G)	-
CTP Surface Hardness	≥6H	-
Brightness	350typ	cd/m2
Contrast Ratio(CR)	300:1	-
Operating Temperature	-20~70	°C
Storage Temperature	-30~80	°C

## 2、EXTERNAL DIMENSIONS



### 3、ABSOLUTE MAXIMUM RATINGS

Parameter of absolute maximum ratings	Symbol	Min	Max	Unit
Operating temperature	Top	-20	70	°C
Storage temperature	Tst	-30	80	°C
Humidity	RH	-	90%(Max 60°C)	RH

Note: Absolute maximum ratings means the product can withstand short-term, not more than 120 hours. If the product is a long time to withstand these conditions, the life time would be shorter.

### 4、ELECTRICAL CHARACTERISTICS(DC CHARACTERISTICS)

Parameter of DC characteristics	Symbol	Min.	Typ.	Max.	Unit
PCB operating voltage	VUSB	-	5.0	-	V
LCD I/O operating voltage	VDD	3.0	3.3	3.6	V
Input voltage 'H' level	VIH	0.7*VDD	-	VDD	V
Input voltage 'L' level	VIL	VSS	-	0.3*VDD	V
Output voltage 'H' level	VOH	VDD-0.4	-	VDD	V
Output voltage 'L' level	VOL	VSS	-	VSS+0.4	V

## 5、CTP CHARACTERISTICS

Item of CTP characteristics	Specification	Unit	Remark
Panel Type	Glass Cover + Glass Sensor	-	-
Resolution	800 × 480	pixel	-
Surface Hardness	≥6H	-	-
Transparency	>82%	-	-
Driver IC	-	-	-
Interface Type	JST-SH 4pin	-	-
Support Points	5(windows) / 1(linux)	-	-
Sampling Rate	20~100	Hz	-
Supply voltage	3.3	V	-

## 6、ELECTRO-OPTICAL CHARACTERISTICS

Item of electro-optical characteristics		Symbol	Condition	Min.	Typ.	Max.	Unit	Remark	Note
Response time		Tr+Tf	$\theta=0$ $\varnothing=0$ Ta=25℃	-	20	-	ms	FIG 1.	4
Contrast Ratio		CR		-	350	-	-	FIG 2.	1
Luminance uniformity		$\delta$ WHITE		-	80	-	%	FIG 2.	3
Surface Luminance		Lv		-	350	-	cd/m2	FIG 2.	2
CIE (x, y) chromaticity	White	White x	$\theta=0$ $\varnothing=0$ Ta=25℃	-	0.317	-	-	FIG 2.	5
		White y		-	0.324	-			
	Red	Red x		-	0.633	-			
		Red y		-	0.341	-			
	Green	Green x		-	0.324	-			
		Green y		-	0.551	-			
	Blue	Blue x		-	0.153	-			
		Blue y		-	0.143	-			
Viewing angle range	$\varnothing=90$ (12 o'clock)		CR $\geq$ 10	-	50	-	deg	FIG 3.	6
	$\varnothing=270$ (6 o'clock)			-	60	-	deg		
	$\varnothing=0$ (3 o'clock)			-	65	-	deg		
	$\varnothing=180$ (9 o'clock)			-	65	-	deg		
NTSC ratio		-	-	50	-	%	-	-	

**Note 1.** Contrast Ratio(CR) is defined mathematically by the following formula. For more information see FIG 2.:

$$\text{Contrast Ratio(CR)} = \frac{\text{Average Surface Luminance with all white pixels(P1,P2, P3, P4, P5, P6, P7, P8, P9)}}{\text{Average Surface Luminance with all black pixels(P1,P2, P3, P4, P5, P6, P7, P8, P9)}}$$

**Note 2.** Surface luminance is the LCD surface from the surface with all pixels displaying white. For more information see FIG 2.

Lv=Average Surface Luminance with all white pixels (P1,P2,P 3,P4, P5,P6,P7,P8,P9)

**Note 3.** The uniformity in surface luminance ( $\delta$ WHITE) is determined by measuring



luminance at each test position 1 through 9, and then dividing the maximum luminance of 9 points luminance by minimum luminance of 9 points luminance. For more information see FIG 2.

$$\delta_{\text{WHITE}} = \frac{\text{Minimum Surface Luminance with all white pixels (P1, P2, P3, P4, P5, P6, P7, P8, P9)}}{\text{Maximum Surface Luminance with all white pixels (P1, P2, P3, P4, P5, P6, P7, P8, P9)}}$$

**Note 4.** Response time is the time required for the display to transition from White to black(Rise Time, Tr) and from black to white(Decay Time, Tf). For additional information see FIG 1.


**Note 5.** CIE (x, y) chromaticity ,The x,y value is determined by screen active area position 5. For more information see FIG 2.

**Note 6.** Viewing angle is the angle at which the contrast ratio is greater than a specific value. For TFT module, the specific value of contrast ratio is 10.The angles are determined for the horizontal or x axis and the vertical or y axis with respect to the z axis which is normal to the LCD surface. For more information see FIG 3.

**Note 7.** For Viewing angle and response time testing, the testing data is base on Autronic-Melchers's ConoScope. Series Instruments. For contrast ratio, Surface Luminance, Luminance uniformity and CIE, the testing data is base on BM-7 photo detector.

**Note 8.** For TN type TFT transmissive module, Gray scale reverse occurs in the direction of panel viewing angle.

**FIG.1. The definition of Response Time**




**FIG.2. Measuring method for Contrast ratio, surface luminance, Luminance uniformity, CIE (x , y) chromaticity**

A : H/6 ;


B : V/6 ;

H,V : Active Area(AA) size

Measurement instrument: BM-7; Light spot size=5mm, 350mm distance from the LCD surface to detector lens.



**FIG.3. The definition of viewing angle**



## 7、INTERFACE DESCRIPTION

### A、HDMI Type-E Interface Description

NO.	Symbol	DESCRIPTION
1	TMDS Data2+	Positive side of channel 2 TMDS low-voltage signal differential input pair
2	TMDS Data2 Shield	Ground
3	TMDS Data2-	Negative side of channel 2 TMDS low-voltage signal differential input pair
4	TMDS Data1+	Positive side of channel 1 TMDS low-voltage signal differential input pair
5	TMDS Data1 Shield	Ground
6	TMDS Data1-	Negative side of channel 1 TMDS low-voltage signal differential input pair
7	TMDS Data0+	Positive side of channel 0 TMDS low-voltage signal differential input pair
8	TMDS Data0 Shield	Ground
9	TMDS Data0-	Negative side of channel 0 TMDS low-voltage signal differential input pair
10	TMDS Clock+	Positive side of reference clock. TMDS low-voltage signal differential input pair
11	TMDS Clock Shield	Ground
12	TMDS Clock-	Negative side of reference clock. TMDS low-voltage signal differential input pair
13	CEC	No Connection
14	Reserved(N.C.)	No Connection
15	SCL	DDC SCL
16	SDA	DDC SDA
17	DDC/CEC Ground	Ground
18	+5V Power	+5V Power
19	Hot Plug Detect	Hot Plug Detect

### B、JST-SH 4pin Interface Description

NO.	Symbol	DESCRIPTION
1	D+	USB Data+
2	D-	USB Data-
3	VUSB	USB Power
4	GND	Power Ground

**Application Note: Please connect the JST-SH first, and then connect the HDMI interface.**

## 8、 LCD TIMING

**Parallel RGB input Timing table**

Parameter	Symbol	Value			Unit
		Min.	Typ.	Max.	
DCLK frequency@ Frame rate=60Hz	DCLK	-	30	50	MHz
Horizontal display area	thd	800			DCLK
1 Horizontal Line	th	-	928	-	DCLK
HSYNC pulse width	thpw	1	48	-	DCLK
HSYNC Back Porch(Blanking)	thb	-	88	-	DCLK
HSYNC Front Porch	thfp	-	40	-	DCLK
Vertical display area	tvd	480			H
VSYNC period time	tv	-	525	-	H
VSYNC pulse width	typw	-	3	-	H
VSYNC Back Porch(Blanking)	tvb	-	32	-	H
VSYNC Front Porch	tvfp	-	13	-	H

## 9、RELIABILITY TEST CONDITIONS

No.	Test Item	Test Condition
1	High Temperature Storage	80°C/120 hours
2	Low Temperature Storage	-30°C/120 hours
3	High Temperature Operating	70°C/120 hours
4	Low Temperature Operating	-20°C/120 hours
5	Temperature Cycle Storage	-20°C(30min.)~25(5min.)~70°C(30min.)×10cycles

### A、 Inspection after test:

Inspection after 2~4 hours storage at room temperature, the sample shall be free from defects:

- Air bubble in the LCD;
- Sealleak;
- Non-display;
- Missing segments;
- Glass crack;
- Current is twice higher than initial value.

### B、 Remark:

- The test samples should be applied to only one test item.
- Sample size for each test item is 5~10pcs.
- Failure Judgment Criterion: Basic Specification, Electrical Characteristic, Mechanical Characteristic, Optical Characteristic.

## 10、 INSPECTION CRITERION

This specification is made to be used as the standard of acceptance/rejection criteria for TFT-LCD/IPS TFT-LCD module product, and this specification is applicable only in the case that the size of module equal to or exceed than 3.5 inch.

### 10.1 Sample plan

Sampling plan according to GB/T2828.1-2003/ISO 2859-1: 1999 and ANSI/ASQC Z1.4-1993,normal level 2 and based on:

Major defect: AQL 0.65


Minor defect: AQL 1.5

### 10.2 Inspection condition

Viewing distance for cosmetic inspection is about 30cm with bare eyes, and under an environment of 20~40W light intensity, all directions for inspecting the sample should be within 45° against perpendicular line. (Normal temperature 20~25°C and normal humidity 60 ±5%RH )

### 10.3 Definition of Inspection Item. A、

Definition of inspection zone in LCD.



Zone A: character/Digit area

Zone B: viewing area except Zone A (Zone A + Zone B=minimum Viewing area)

Zone C: Outside viewing area (invisible area after assembly in customer's product)

Fig.1 Inspection zones in an LCD

Note: As a general rule, visual defects in Zone C are permissible, when it is no trouble for quality and assembly of customer's product.


### B、 Definition of some visual defect

Bright dot	Because of losing all or part function, bad pixel dots appear bright and the size is more than 50% of one dot in which LCD panel is displaying under black pattern.
Dark dot	Dots appear dark and unchanged in size in which LCD panel is displaying under pure red, green, blue picture, or pure whiter picture.

### 10.4 Major Defect




Item No.	Items to be inspected	Inspection standard	Classification of defects
1	Functional defects	1) No display 2) Display abnormally 3) Missing vertical, horizontal segment 4) Short circuit 5) Excess power consumption 6) Backlight no lighting, flickering and abnormal lighting	major
2	Missing	Missing component	
3	Outline dimension	Overall outline dimension beyond the drawing is not allowed	

10.5 Minor Defect

Item No.	Items to be inspected	Inspection standard					Classification of defects
1	Bright dot /dark dot defect	Zone		Acceptable Qty			Minor
				A+B			
		3.5''~7''	7~10.1''	>10.1''	Acceptable		
	Bright pixel dot	1	2	3			
	Dark pixel dot	4	4	4			
	2bright dots adjacent	0	0	0			
	2dark dots adjacent	0	0	0			
	Total bright and dark dots	5	6	7			
Note: Minimum distance between defective dots is more than 5mm; Pixel dots' function is normal, but bright dots caused by foreign material and other reasons are judged by the dot defect of 5.2.							
2	Dot defect  $\Phi = (x+y) / 2$	Zone		Acceptable Qty			Minor
				A+B			
Size(mm)		3.5''~7''	7~10.1''	>10.1''	Acceptable		
	$\Phi \leq 0.2$	Acceptable	Acceptable	Acceptable			
	$0.2 < \Phi \leq 0.5$	4	5	6			
	$\Phi > 0.5$	0	0	0			
Note: 1. Minimum distance between defective dots is more than 5 mm; 2. The quantity of defect is zero in operating condition.							
3	Linear defect	Zone		Acceptable Qty			Minor
Size (mm)				A+B			
	Length	Width	3.5''~7''	7~10.1''	>10.1''		
	Ignore	$W \leq 0.05$	Acceptable	Acceptable	Acceptable	Acceptable	
	$L \leq 5.0$	$0.05 < W \leq 0.1$	4	5	6		
	$L > 5.0$	$W > 0.1$	0	0	0		



4	Polarizer defect	<p>5.4.1 Polarizer Position</p> <p>(i) Shifting in position should not exceed the glass outline dimension.</p> <p>(ii) Incomplete covering of the viewing area due to shifting is not allowed.</p> <p>5.4.2 Dirt on polarizer</p> <p>Dirt which can be wiped easily should be acceptable.</p> <p>5.4.3 Polarizer Dent &amp; Air bubble</p> <table border="1" data-bbox="464 517 1235 835"> <thead> <tr> <th colspan="2" rowspan="2">Zone</th> <th colspan="3">Acceptable Qty</th> <th rowspan="2">C</th> </tr> <tr> <th colspan="3">A+B</th> </tr> <tr> <th colspan="2">Size(mm)</th> <th>3.5''~7''</th> <th>7~10.1''</th> <th>&gt;10.1''</th> <th rowspan="4">Acceptable</th> </tr> </thead> <tbody> <tr> <td colspan="2"><math>\Phi \leq 0.2</math></td> <td>Acceptable</td> <td>Acceptable</td> <td>Acceptable</td> </tr> <tr> <td colspan="2"><math>0.2 &lt; \Phi \leq 0.5</math></td> <td>4</td> <td>5</td> <td>6</td> </tr> <tr> <td colspan="2"><math>\Phi &gt; 0.5</math></td> <td>0</td> <td>0</td> <td>0</td> </tr> </tbody> </table> <p>5.4.4 Polarizer scratch</p> <p>(i) If the polarizer scratch can be seen after cover assembling or in the operating condition, judge by the linear defect of 5.3.</p> <p>(ii) If the polarizer scratch can be seen only in non-operating condition or some special angle, judge by the following:</p> <table border="1" data-bbox="464 1043 1235 1444"> <thead> <tr> <th colspan="2" rowspan="2">Zone</th> <th colspan="3">Acceptable Qty</th> <th rowspan="2">C</th> </tr> <tr> <th colspan="3">A+B</th> </tr> <tr> <th>Length</th> <th>Width</th> <th>3.5''~7''</th> <th>7~10.1''</th> <th>&gt;10.1''</th> <th rowspan="4">Acceptable</th> </tr> </thead> <tbody> <tr> <td>Ignore</td> <td><math>W \leq 0.05</math></td> <td>Acceptable</td> <td>Acceptable</td> <td>Acceptable</td> </tr> <tr> <td><math>1.0 &lt; L \leq 5.0</math></td> <td><math>0.05 &lt; W \leq 0.20</math></td> <td>4</td> <td>5</td> <td>6</td> </tr> <tr> <td><math>L &gt; 5.0</math></td> <td><math>W &gt; 0.2</math></td> <td>0</td> <td>0</td> <td>0</td> </tr> </tbody> </table>	Zone		Acceptable Qty			C	A+B			Size(mm)		3.5''~7''	7~10.1''	>10.1''	Acceptable	$\Phi \leq 0.2$		Acceptable	Acceptable	Acceptable	$0.2 < \Phi \leq 0.5$		4	5	6	$\Phi > 0.5$		0	0	0	Zone		Acceptable Qty			C	A+B			Length	Width	3.5''~7''	7~10.1''	>10.1''	Acceptable	Ignore	$W \leq 0.05$	Acceptable	Acceptable	Acceptable	$1.0 < L \leq 5.0$	$0.05 < W \leq 0.20$	4	5	6	$L > 5.0$	$W > 0.2$	0	0	0	Minor
Zone		Acceptable Qty			C																																																										
		A+B																																																													
Size(mm)		3.5''~7''	7~10.1''	>10.1''	Acceptable																																																										
$\Phi \leq 0.2$		Acceptable	Acceptable	Acceptable																																																											
$0.2 < \Phi \leq 0.5$		4	5	6																																																											
$\Phi > 0.5$		0	0	0																																																											
Zone		Acceptable Qty			C																																																										
		A+B																																																													
Length	Width	3.5''~7''	7~10.1''	>10.1''	Acceptable																																																										
Ignore	$W \leq 0.05$	Acceptable	Acceptable	Acceptable																																																											
$1.0 < L \leq 5.0$	$0.05 < W \leq 0.20$	4	5	6																																																											
$L > 5.0$	$W > 0.2$	0	0	0																																																											
5	MURA  White/Black dot (MURA)	<p>Using 3% ND filter, it's NG if it can be seen in R,G,B picture.</p> <p>Visible under: ND3%; <math>D \leq 0.15\text{mm}</math>, Acceptable;  <math>0.15\text{mm} &lt; D \leq 0.5\text{mm}</math>, <math>N \leq 4</math>; <math>D &gt; 0.5\text{mm}</math>, Not allowable.</p>	Minor																																																												

6	Glass defect	<p>(i) Crack Cracks are not allowed.</p> 	Minor								
		<p>(ii) TFT chips on corner</p>  <table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th style="width: 25%;">X</th> <th style="width: 25%;">Y</th> <th style="width: 25%;">Z</th> <th style="width: 25%;">Acceptable</th> </tr> </thead> <tbody> <tr> <td style="text-align: center;"><math>\leq 3.0</math></td> <td style="text-align: center;"><math>\leq 3.0</math></td> <td style="text-align: center;">Not more than the thickness of glass</td> <td style="text-align: center;"><math>N \leq 3</math></td> </tr> </tbody> </table> <p>Chips on the corner of terminal shall not be allowed to extend into the ITO pad or expose perimeter seal.</p>	X	Y	Z	Acceptable	$\leq 3.0$	$\leq 3.0$	Not more than the thickness of glass	$N \leq 3$	Minor
		X	Y	Z	Acceptable						
$\leq 3.0$	$\leq 3.0$	Not more than the thickness of glass	$N \leq 3$								
<p>(iii) Usual surface crack</p>  <table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th style="width: 25%;">X</th> <th style="width: 25%;">Y</th> <th style="width: 25%;">Z</th> <th style="width: 25%;">Acceptable</th> </tr> </thead> <tbody> <tr> <td style="text-align: center;"><math>\leq 1.5</math></td> <td style="text-align: center;"><math>\leq 1.5</math></td> <td style="text-align: center;">Not more than the thickness of glass</td> <td style="text-align: center;"><math>N \leq 4</math></td> </tr> </tbody> </table> <p style="text-align: center;">It is only applicable to the upper glass of LCD.</p>	X	Y	Z	Acceptable	$\leq 1.5$	$\leq 1.5$	Not more than the thickness of glass	$N \leq 4$	Minor		
X	Y	Z	Acceptable								
$\leq 1.5$	$\leq 1.5$	Not more than the thickness of glass	$N \leq 4$								

## 10.6 Module Cosmetic Criteria

Item No.	Items to be inspected	Inspection Standard	Classification of defects
1	Difference in Spec.	Not allowable	Major
2	Pattern peeling	No substrate pattern peeling and floating	Major
3	Soldering defects	No soldering missing	Major
		No soldering bridge	Major
		No cold soldering	Minor
4	Resist flaw on PCB	Visible copper foil ( $\Phi 0.5$ mm or more) on substrate pattern is not allowed	Minor
5	FPC gold finger	No dirt, breaking, oxidation lead to black	Major
6	Backlight plastic frame	No deformation, crack, breaking, backlight positioning column breaking, obvious nick.	Minor
7	Marking printing effect	No dark marking, incomplete, deformation lead to unable to judge	Minor
8	Accretion of metallic Foreign matter	No accretion of metallic foreign matter (Not exceed $\Phi 0.2$ mm)	Minor
9	Stain	No stain to spoil cosmetic badly	Minor
10	Plate discoloring	No plate fading, rusting and discoloring	Minor
11	1. Lead parts	a. Soldering side of PCB Solder to form a 'Filet' all around the lead. Solder should not hide the lead form perfectly.	Minor
		b. Components side(In case of 'Through Hole PCB') Solder to reach the Components side of PCB.	Minor
	2. Flat packages	Either 'Toe'(A) or 'Seal'(B)of the lead to be covered by "Filet". Lead form to be assume over Solder. 	Minor
	3. Chips	$(3/2) H \geq h \geq (1/2) H$ 	Minor
4. Solder ball/Solder splash	a. The spacing between solder ball and the conductor or solder pad $h \geq 0.13$ mm. The diameter of solder ball $d \leq 0.15$ mm.	Minor	
	b. The quantity of solder balls or solder splashes isn't beyond 5 in 600 mm <sup>2</sup> .	Minor	
	c. Solder balls/Solder splashes do not violate minimum electrical clearance.	Major	

huayuan display technology CO.,LTD